

General Product Specifications

Imperea Scanners

Device Charging	Custom power adapter included with the single station wireless charger (12V 1.5A, 18W)
Compatibility	iPhone SE (2020), iPhone 8, iPhone 7, and iPhone 6/6S*
Input Voltage	5 Volts
Barcode Scanner	Enterprise-grade 2D Camera Scanning Decoder Engine
OCR Scanner	OCR-A, OCR-B, MICR E-13B, SEMI
Barcode Types	Supports all major 1D or 2D barcodes, including 1D symbologies: Code 39, Code 93, Code 128, UPC/EAN/JAN, Interleaved 2 of 5, Hong Kong 2 of 5, Matrix 2 of 5, NEC 2 of 5, Codabar, Code 11, MSI Plessey, Pharmacode, RSS, Telepen, Straight 2 of 5, Korea Post, Trioptic 2D symbologies: Data Matrix, PDF417, MicroPDF417, QR Code, Micro QR Code, Aztec Code, Codablock, MaxiCode, UCC Composite, Hanxin, DotCode, Grid Matrix, OCR-A, OCR-B, MICR E-13B, SEMI
Protection Features	IP67 Waterproof and Dustproof Built-in antimicrobial materials, Protective tempered glass, Sanitation compatible.
Drop Rating	MIL-STD-810 4ft to concrete drop protection rating
LEDs	4 LEDs battery status indicators
LEDs Buttons	4 LEDs battery status indicators 3 app/SDK controllable buttons. Battery status button on the battery. *All existing iOS buttons are accessible
	3 app/SDK controllable buttons. Battery status button on the battery.
Buttons	3 app/SDK controllable buttons. Battery status button on the battery. *All existing iOS buttons are accessible User removable/swappable, rechargeable battery. Capacity
Buttons	3 app/SDK controllable buttons. Battery status button on the battery. *All existing iOS buttons are accessible User removable/swappable, rechargeable battery. Capacity 2100mAh. Supports Wireless Charging Access to Apple iphone Audio speakers and microphone. Access
Buttons Battery Audio/Visual Indicators	3 app/SDK controllable buttons. Battery status button on the battery. *All existing iOS buttons are accessible User removable/swappable, rechargeable battery. Capacity 2100mAh. Supports Wireless Charging Access to Apple iphone Audio speakers and microphone. Access to Apple Iphone front and back camera Operating temperature: -0°C to +40°C (+32°F to +104°F) Operating humidity: 5% to 90% Relative Humidity Storage temperature: -20°C to +65°C (-4°F to +149°F)
Buttons Battery Audio/Visual Indicators Operating Environment	3 app/SDK controllable buttons. Battery status button on the battery. *All existing iOS buttons are accessible User removable/swappable, rechargeable battery. Capacity 2100mAh. Supports Wireless Charging Access to Apple iphone Audio speakers and microphone. Access to Apple Iphone front and back camera Operating temperature: -0°C to +40°C (+32°F to +104°F) Operating humidity: 5% to 90% Relative Humidity Storage temperature: -20°C to +65°C (-4°F to +149°F) Storage humidity: 5% to 90% Relative Humidity
Buttons Battery Audio/Visual Indicators Operating Environment Dimensions	3 app/SDK controllable buttons. Battery status button on the battery. *All existing iOS buttons are accessible User removable/swappable, rechargeable battery. Capacity 2100mAh. Supports Wireless Charging Access to Apple iphone Audio speakers and microphone. Access to Apple Iphone front and back camera Operating temperature: -0°C to +40°C (+32°F to +104°F) Operating humidity: 5% to 90% Relative Humidity Storage temperature: -20°C to +65°C (-4°F to +149°F) Storage humidity: 5% to 90% Relative Humidity 160mm x 76.6mm x 18.6mm (Length x Width x Depth)



www.stimare.net www.lineapro.store info@stimare.net info@lineapro.store

USA +1-720-257-7070 UK +44-208-0998071 Ireland +353-1-6854600

We are the experts in:

BARCODE SCANNING

MOBILE PRINTING

POINT-OF-SALE (POS)

^{*}iPhone 6/6S headphone jack will be blocked using the Imperea