



General Product Specifications

Linea Pro 6 MSR

Power Supply	5V through mini USB or station charger
Compatibility	iPhone 6/6s
Power Consumption	Deep sleep -20uA
Magnetic Stripe Reader	3-track bidirectional reading capabilities Type: ISO 7810, 7811, 7813
Barcode Scanner	No scan engine
Encryption and Key (optional)	Encryption capable MSR. 3DES-112, AES 128/256, DUKPT
LEDs	4 LEDs for battery status
Buttons	Battery status button
Battery	2040mAh battery
Cables	Standard USB A to mini B cable
Audio Indicator	Electromagnetic Buzzer
Operating Environment	Operating temperature: 0°C to +40°C Operating humidity: 35 to 85% RH Storage temperature: -5°C to +40°C Storage humidity: 10 to 90% RH
Dimensions	1D scanner 157mm x 77mm x 22mm 2D scanner 142mm x 69mm x 27mm
Weight	147 grams
Software Support	SDK for iOS platform
Certifications	CE, FCC, Apple Mfi, Optional PCI Compliance (PCI PTS 3.x SRED)



www.stimare.net
www.lineapro.store
info@stimare.net
info@lineapro.store

USA +1-720-257-7070
UK +44-208-0998071
Ireland +353-1-6854600

We are the experts in:
BARCODE SCANNING
MOBILE PRINTING
POINT-OF-SALE (POS)