



General Product Specifications

Linea Pro Rugged XR / 11

Power Supply	5V through USB C-Type or Station charger
Compatibility	iPhone XR and iPhone 11
Power Consumption	Deep sleep -20uA
Barcode Scanner	Zebra SE4750 2D White LED illumination with Red LED dot aimer
Bluetooth (optional)	Bluetooth 3.0 compatible - Class 2 - Serial Port Profile (SPP) - iAP
Barcode Type	Supports all major 1D or 2D barcodes, including 1D symbologies: EAN/UPC, GS1 Databar (limited expanded & omni-directional), RSS, Code 39, Code 128,UCC/EAN 128, ISBN, ISBT, Interleaved/Matrix/Industrial and Standard 2 of 5, Codabar, Code 93/93i, Code 11, MSI, Plessey, Telepen. Postal codes2D symbologies: Data Matrix, Reversed Data Matrix, PDF417, Micro PDF417, Codablock, Maxicode, QR, Aztec, GS1 composite codes.
HF RFID Reader (optional)	MiFARE Mini MiFARE Classic 1K / 4K MiFARE Ultra-Light / Ultra-Light-C MiFARE Plus 2K / 4K ISO / IEC 14443 Type A/B ISO / IEC 15693 MiFARE DESFire JIS X 6319-4 (compatible with FelICA
UHF RFID Reader (optional)	ISO 18000-6C / EPC Gen2 V2 Compatible Bands: Narrow US band (Wide US band), Korea Band, China band, Japan band, EU band, Brazil band
NFC /Contactless Payments (optional)	Apple VAS Google Smart Tap
Buttons	Dual-Scanning buttons
Battery	3.7v 2400mAh battery (16,850 Scans over approx. 26hrs of use)
Cables	USB Type-C for device charge and sync
Audio Indicator	Electromagnetic Buzzer
Operating Environment	Operating temperature: -10°C to +40°C Operating humidity: 5 to 90% RH Storage temperature: -15°C to +50°C Storage humidity: 5 to 90% RH
Dimensions	(LxWxH): 170 mm x 85 mm x 26 mm (6.69 in x 3.35 in x 1.02 in)
Weight	175 grams (6.2 oz.) without iOS Device
Software Support	SDK for iOS platform, Qwedge
Certifications	CE, FCC, Apple Mfi, RoHS, IP65, MIL-STD-810G



www.stimare.net

www.lineapro.store

info@stimare.net

info@lineapro.store

USA +1-720-257-7070

UK +44-208-0998071

Ireland +353-1-6854600

We are the experts in:

BARCODE SCANNING

MOBILE PRINTING

POINT-OF-SALE (POS)