

Infinea mPOS



Battery	Rechargeable Li-ion battery 3.7V / 1330mAh
Battery Life	Over 10,000 scans and swipes per full charge
Compatibility	iPhone 5/5s, iPhone SE, iPod Touch 5 and 6
Barcode Scanner	Newland EM3080 - Image Sensor 640x480 CMOS CMOS
Card Reader	3-track bidirectional Magnetic Stripe Reader (MSR)
Smart Card Reader	ISO7816, EMV L1 certified
NFC	AMEX ExpressPay, MagStripe and EMV Discover ZIP and D-PAS MasterCard PayPass MagStripe and M/Chip VISA PayWave MSD and qVSDC
Port	Mini USB for charge and sync
LEDs	4 LEDs for transaction and device status
Audio Indicator	Electromagnetic buzzer
Operating Environment	Temperature: -10°C to +40°C (14°F to +104°F) Humidity: 5% to 90% RH
Storage Environment	Temperature: -20°C to +50°C (4°F to +122°F) Humidity: 5% to 90% RH
Dimensions	145mm x 68mm x 27mm (5.7" x 2.7" x .1.1")
Weight	188 grams (6.63 oz.) without iOS device
Certifications	Apple MFi

www.stimare.net

www.lineapro.store

info@stimare.net

info@lineapro.store

USA +1-720-257-7070

UK +44-208-0998071

Ireland +353-1-6854600

We are the experts in:

BARCODE SCANNING

MOBILE PRINTING

POINT-OF-SALE (POS)