

## General Product Specifications

# Sewoo 2" Printers: LK-P12

<b>Printing Method</b>	Direct thermal
<b>Printing Speed</b>	100mm/sec
<b>Printing Width</b>	48mm
<b>Resolution</b>	203dpi (8x9 dots/mm)
<b>Barcodes Printed</b>	1D: EAN-8, EAN-13, EAN-128, Postnet, Code39, Code93, Code128, Codabar, ITF, UPC-A, UPC-E 2D: PDF417, QR Code, Maxicode, GS1 / DataBar™ (RSS) family, Datamatrix, Aztec
<b>Fonts</b>	Internal font: Font A, Font B, Download bitmap and true type font
<b>Paper Width</b>	12.7~58mm
<b>Roll diameter</b>	Max. Ø 56mm
<b>Connectivity</b>	Standard USB Serial RS232C Wi-Fi (802.11 a/b/g) (optional) Bluetooth Class 2 (optional)
<b>Internal Memory</b>	SDRAM: 8MB FLASH: 16MB
<b>Sensors</b>	Paper end Gap Black mark Cover open
<b>Additional Features</b>	Peeler (optional)
<b>Emulation</b>	ESC/POS, CPCL, ZPL Command compatible
<b>Operating Environment</b>	Operating temperature: -10 - 50°C (14 - 122°F) Operating humidity: 10 ~ 90%
<b>Storage Environment</b>	Storage temperature: -20 - 60°C (-4 - 140°F) Storage humidity: 10 ~ 90%
<b>Drop Resistance</b>	1.5m (5ft) onto concrete
<b>IP Rating</b>	IP42
<b>Dimensions</b>	W x D x H(mm): 100x158x85 W x D x H(inch): 3.93x6.22x3.34
<b>Weight</b>	580g (with battery)
<b>Drivers</b>	Windows Driver (2012, 8, 7, 2008, VISTA, 2003, XP, 32bit & 64bit), Window CE & Mobile Driver & SDK(CE 4.2~, Mobile 5.0~), Linux Driver, Mac Driver, OPOS Driver, JavaPOS Driver, iOS SDK, Android (2.1~) SDK, Blackberry SDK, Symbian
<b>Battery</b>	7.4V / 2200mAh, 2600mAh Li-ion, 3.3 Hrs Charging Time, 85 Hrs Stand-by (2600mAh) AC/DC charger



[www.stimare.net](http://www.stimare.net)  
[www.lineapro.store](http://www.lineapro.store)  
[info@stimare.net](mailto:info@stimare.net)  
[info@lineapro.store](mailto:info@lineapro.store)

**USA** +1-720-257-7070  
**UK** +44-208-0998071  
**Ireland** +353-1-6854600

We are the experts in:  
**BARCODE SCANNING**  
**MOBILE PRINTING**  
**POINT-OF-SALE (POS)**