

General Product Specifications

Sewoo 4" Printers: LK-P43

Printing Method	Direct thermal
Printing Speed	80mm/sec
Printing Width	104mm
Resolution	203 DPI
Barcodes Printed	1D: EAN-8, EAN-13, EAN-128, Postnet, Code39, Code93, Code128, Codabar, ITF, UPC-A, UPC-E 2D: PDF417, QR Code, Maxicode, GS1 / DataBar™ (RSS) family, Datamatrix, Aztec
Paper Width	50mm - 112mm
Roll diameter	Max. Ø 56mm
Connectivity	Standard USB Serial RS232C Wi-Fi (802.11 a/b/g) (optional) Bluetooth Class 2 (optional)
Internal Memory	SDRAM: 16MB FLASH: 32MB
Sensors	Paper end Gap Black mark Cover open
Additional Features	Peeler (optional)
Emulation	ESC/POS, CPCL, ZPL Command compatible
Operating Environment	Operating temperature: -21 - 55°C (14 - 122°F) Operating humidity: 10 ~ 90%
Storage Environment	Storage temperature: -30 - 65°C (-4 - 140°F) Storage humidity: 10 ~ 90%
Drop Resistance	1.8m (6ft) onto concrete
IP Rating	IP54
LCD	Color graphic LCD 128 x 64 dots
Dimensions	W x D x H(mm): 154×174×80 W x D x H(inch): 6×6.8×3.1
Weight	1kg (with 2600mAh battery)
Battery	7.4V / 2600mAh, 5200mAh Li-ion, 6.2Hrs Charging Time, 108.3 Hrs Stand-by (5200mAh) AC/DC charger



www.stimare.net

www.lineapro.store

info@stimare.net

info@lineapro.store

USA +1-720-257-7070

UK +44-208-0998071

Ireland +353-1-6854600

We are the experts in:

BARCODE SCANNING

MOBILE PRINTING

POINT-OF-SALE (POS)