



General Product Specifications

Sewoo POS Printers: LK-TE25



Printing Method	Direct thermal
Printing Speed	200mm/sec
Printing Width	72mm (512 Dots/Line)
Resolution and Pitch	180 DPI; Pitch: 0.141mm x 0.141mm
Barcodes Printed	EAN-8, EAN-13, Code 39, Code 93, Code 128, ITF, UPC-A, UPC-E, Codabarr
Characters per Line	Font A (12x24): 42 columns Font B (9x17): 56 columns
Paper Width	80mm
Paper Thickness	0.06mm ~ 0.09mm
Roll diameter	Max. Ø 83 mm (core roll inner diameter 12.5 mm ± 0.5 mm)
Connectivity	Standard USB Serial RS232C (optional) Wi-Fi (optional) Bluetooth (optional) Ethernet (optional) Parallel (optional)
Power	Type: External SMPS AC: 100 ~ 240Vac 50/60 Hz DC: 24Vdc / 1.75A
Auto Cutter	Type: Guillotine Life: 1,500,000 cuts Cutting method: Full / Partial Cut
Sensors	Standard: Paper end, Gap, Cover open Optional: Black mark
Cash Drawer	2 circuits (24V, 1A max)
Reliability	TPH LIFE: 160 km MCBF: 60 million Lines
Emulation	ESC/POS command compatible
Operating Environment	Operating temperature: 0 - +45°C (32 - 113°F) Operating humidity: 35 ~ 80%
Storage Environment	Storage temperature: -20 - +60°C (-4 - 140°F) Storage humidity: 10 ~ 90%
Dimensions	W x D x H(mm) : 125 x 200 x 112.5 W x D x H(inch) : 4.92 x 7.87 x 4.43
Weight	1.4kg
Certifications	FCC, KCC, UL/cUL
Driver	Windows Driver (2012, 8, 7, 2008, VISTA, 2003, XP, 32bit & 64bit), Windows CE & Mobile Driver & SDK (CE 4.2 ~, Mobile 5.0 ~), Linux Driver, Mac Driver, OPOS Driver, JavaPOS Driver, iOS SDK, Android (2.1 ~) SDK, Windows SDK

www.stimare.net

www.lineapro.store

info@stimare.net

info@lineapro.store

USA +1-720-257-7070

UK +44-208-0998071

Ireland +353-1-6854600

We are the experts in:

BARCODE SCANNING

MOBILE PRINTING

POINT-OF-SALE (POS)